

KS 1010GLIDER[™]







Lock lever

Buggle or star b



Place your order by contacting us on: +49 5244 9079 50 Order.Kintec@Leggett.com

KS 1010GLIDER[™]

KS 1010 Glider by Kintec Solution, an outstanding motion furniture component for chairs and footstools. Simply effortless gliding back and forth motion that feels naturally calming. The glider base also features a 360-degree rotation spin function, perfect for home, leisure or work environments.

Patented Technology - Products safeguarded by international patents.

Key Features & Benefits				
Available for	All Kintec swivel base seati	ing solutions.	KS Swivels unique features:	
Function	Glide back and forth, 360-degree.		Natural gliding motion.	
	rotation spin.		Full continuous 360-degree or 340-degree ro	tation.
Operation	Manual operation.		Made from strong, durable materials.	
Installation	Attached to swivel base.		Easy to install.	
		Motion	Features	
Glide			Rotation	
Back and forth motior			Full unrestricted continuous 360-degree	0
along one central		2011	rotational spin or restrict the rotation by	
pivot point.		J.	using a 340-degree column with stopper.	ク
Reinforced pedest	tal column	\square	Pedestal base	
			More options	
Available in aluminium or black powder coate			available, refer	
Multiple colour finishe	es available		to pedestal	
			haco haoohuno	
			base brochure.	(I)
For glider mechanism it is recommended to	ns durability, use Aluminium	Black powder		ır flat base
For glider mechanism it is recommended to	ns durability, use Aluminium	Black powder coated column		ar flat base
For glider mechanism it is recommended to reinforced pedestal co	s durability, use Aluminium olumns only. column c	coated column	Lentil base 5 sta	
For glider mechanism it is recommended to reinforced pedestal co Reinforced swivels	s durability, use Aluminium olumns only. column co 027 02 20112 65 Sv 027 02 20132 65 Sv	coated column wivel-column f. con wivel-column f. con	Lentil base 5 sta e-base 112,5/ 66ig x Ø50 tapered; alu nature - passivated; reinf e-base 132,5/ 86ig x Ø50 tapered; alu nature - passivated; reinf	orced
For glider mechanism it is recommended to reinforced pedestal or Reinforced swivels options for glider	s durability, use Aluminium olumns only. column co 027 02 20112 65 Sv 027 02 20132 65 Sv 027 02 20142 01 Sv	coated column wivel-column f. con wivel-column f. con wivel-column f. cor	Lentil base 5 sta e-base 112,5/ 66lg x Ø50 tapered; alu nature - passivated; reinf e-base 132,5/ 86lg x Ø50 tapered; alu nature - passivated; reinf ne-base 142,5/ 96lg x Ø50 tapered; black; reinforced	forced
For glider mechanism it is recommended to reinforced pedestal or Reinforced swivels options for glider	s durability, use Aluminium olumns only. column c 027 02 20112 65 Sv 027 02 20132 65 Sv 027 02 20142 01 Sv 027 02 20142 65 Sv	vivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con	Lentil base 5 sta e-base 112,5/ 66lg x Ø50 tapered; alu nature - passivated; reinf e-base 132,5/ 86lg x Ø50 tapered; alu nature - passivated; reinf ne-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror	forced
For glider mechanism it is recommended to reinforced pedestal or Reinforced swivels options for glider	s durability, use Aluminium olumns only. column c 027 02 20112 65 Sv 027 02 20132 65 Sv 027 02 20142 01 Sv 027 02 20142 65 Sv 027 02 20172 01 Sv	coated column wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con	Lentil base 5 sta e-base 112,5/ 66lg x Ø50 tapered; alu nature - passivated; reinf e-base 132,5/ 86lg x Ø50 tapered; alu nature - passivated; reinf ne-base 142,5/ 96lg x Ø50 tapered; black; reinforced	iorced iorced
For glider mechanism it is recommended to reinforced pedestal co Reinforced swivels options for glider mechanisms	s durability, use Aluminium olumns only. column c 027 02 20112 65 Sv 027 02 20132 65 Sv 027 02 20142 01 Sv 027 02 20142 65 Sv 027 02 20172 01 Sv	vivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con	Lentil base 5 sta e-base 112,5/ 66lg x Ø50 tapered; alu nature - passivated; reinf e-base 132,5/ 86lg x Ø50 tapered; alu nature - passivated; reinf ne-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; stror	iorced iorced
depending on quantity For glider mechanism it is recommended to reinforced pedestal or Reinforced swivels options for glider mechanisms Glider Lock BOM Part	A durability, use Aluminium olumns only. column of 027 02 20112 65 Sv 027 02 20132 65 Sv 027 02 20142 01 Sv 027 02 20142 65 Sv 027 02 20172 01 Sv 027 02 20172 65 Sv 027 02 20172 65 Sv	coated column wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con	Lentil base 5 sta e-base 112,5/ 66lg x Ø50 tapered; alu nature - passivated; reinf e-base 132,5/ 86lg x Ø50 tapered; alu nature - passivated; reinf ne-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf	iorced iorced ng nforced QTY per se
For glider mechanism it is recommended to reinforced pedestal or Reinforced swivels options for glider mechanisms Glider Lock BOM	s durability, use Aluminium olumns only. column co 027 02 20112 65 Sv 027 02 20132 65 Sv 027 02 20142 01 Sv 027 02 20142 65 Sv 027 02 20142 65 Sv 027 02 20172 01 Sv 027 02 20172 65 Sv Product Code De 007 03 00011 00 Re	coated column wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con escription elease adapter for	Lentil base 5 sta e-base 112,5/ 66lg x Ø50 tapered; alu nature - passivated; reinf e-base 132,5/ 86lg x Ø50 tapered; alu nature - passivated; reinf ne-base 142,5/ 96lg x Ø50 tapered; black; reinforced e-base 142,5/ 96lg x Ø50 tapered; black; reinforced e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; rein e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; rein	forced forced ng nforced QTY per se 1
For glider mechanism it is recommended to reinforced pedestal of Reinforced swivels options for glider mechanisms Glider Lock BOM Part	Aluminium olumns only. Aluminium olumns only. column of 027 02 20112 65 Sv 027 02 20132 65 Sv 027 02 20142 01 Sv 027 02 20142 65 Sv 027 02 20172 01 Sv 027 02 20172 65 Sv 027 027 02 20172 65 Sv 027 027 027 027 027 027 027 027 027 027	coated column wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con escription elease adapter for letal plate small, 1	Lentil base 5 sta e-base 112;5/ 66ig x Ø50 tapered; alu nature - passivated; reinf e-base 132;5/ 86ig x Ø50 tapered; alu nature - passivated; reinf ne-base 142;5/ 96ig x Ø50 tapered; black; reinforced e-base 142;5/ 96ig x Ø50 tapered; alu nature - passivated; stror e-base 172;5/126ig x Ø50 tapered; alu nature - passivated; reinf e-base 172;5/126ig x Ø50 tapered; alu nature - passivated; reinf e-base 172;5/126ig x Ø50 tapered; alu nature - passivated; reinf e-base 172;5/126ig x Ø50 tapered; alu nature - passivated; reinf e-base 172;5/126ig x Ø50 tapered; alu nature - passivated; reinf e-base 172;5/126ig x Ø50 tapered; alu nature - passivated; reinf e-base 172;5/126ig x Ø50 tapered; alu nature - passivated; reinf	iorced iorced ng nforced QTY per se 1 1
For glider mechanism it is recommended to reinforced pedestal of Reinforced swivels options for glider mechanisms Glider Lock BOM Part	s durability, use Aluminium olumns only. column co 027 02 20112 65 Sv 027 02 20132 65 Sv 027 02 20142 01 Sv 027 02 20142 65 Sv 027 02 20172 01 Sv 027 02 20172 65 Sv 027 02 20172 65 Sv 027 03 00011 00 Re 418 03 00002 10 Mi 418 03 00003 10 Mi	coated column wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con escription elease adapter for	Lentil base 5 sta e-base 112,5/ 66lg x Ø50 tapered; alu nature - passivated; reinf e-base 132,5/ 86lg x Ø50 tapered; alu nature - passivated; reinf ne-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 142,5/ 126lg x Ø50 tapered; alu nature - passivated; stror e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf ne-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - p	forced forced ng nforced QTY per se 1
For glider mechanism it is recommended to reinforced pedestal of Reinforced swivels options for glider mechanisms Glider Lock BOM Part	is durability, use Aluminium columns only. Aluminium column 027 02 20112 65 Sv 027 02 20132 65 Sv 027 02 20142 01 Sv 027 02 20142 65 Sv 027 02 20142 65 Sv 027 02 20172 01 Sv 027 02 20172 65 Sv 027 03 00011 00 Re 418 03 00002 10 M 418 03 00003 10 M 418 03 00005 09 Lo 418 03 00005 09 Lo 418 03 00005 09 Lo	coated column wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con escription elease adapter for tetal plate large, 1 letal plate large, 1 acket Bowden ca	Lentil base 5 sta e-base 112,5/ 66lg x Ø50 tapered; alu nature - passivated; reinf e-base 132,5/ 86lg x Ø50 tapered; alu nature - passivated; reinf ne-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature -	iorced iorced oforced QTY per se 1 1 1 1 1 1 1
For glider mechanism it is recommended to reinforced pedestal of Reinforced swivels options for glider mechanisms Glider Lock BOM Part	is durability, use Aluminium columns only. Aluminium column 027 02 20112 65 Sv 027 02 20132 65 Sv 027 02 20142 01 Sv 027 02 20142 65 Sv 027 02 20142 65 Sv 027 02 20172 01 Sv 027 02 20172 65 Sv 027 03 00011 00 Re 418 03 00002 10 Mi 418 03 00005 09 Lo 418 03 00005 09 Lo 418 03 00005 10 Br 990 15 00141 10 Co	coated column wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con escription elease adapter for letal plate small, 1 etal plate large, 1 worker Bowden ca buntersunk head s	Lentil base 5 sta e-base 112,5/ 66lg x Ø50 tapered; alu nature - passivated; reinf e-base 132,5/ 86lg x Ø50 tapered; alu nature - passivated; reinf ne-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf	iorced iorced ng nforced 0TY per se 1 1 1 1 1 1 5
For glider mechanism it is recommended to reinforced pedestal of Reinforced swivels options for glider mechanisms Glider Lock BOM Part	is durability, use Aluminium columns only. Aluminium column 027 02 20112 65 Sv 027 02 20132 65 Sv 027 02 20142 01 Sv 027 02 20142 65 Sv 027 02 20142 65 Sv 027 02 20172 01 Sv 027 02 20172 65 Sv 027 03 00011 00 Re 418 03 00002 10 Mi 418 03 00005 09 Lo 418 03 00005 09 Lo 418 03 00005 10 Br 990 15 00141 10 Co	coated column wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con escription elease adapter for tetal plate large, 1 letal plate large, 1 acket Bowden ca	Lentil base 5 sta e-base 112,5/ 66lg x Ø50 tapered; alu nature - passivated; reinf e-base 132,5/ 86lg x Ø50 tapered; alu nature - passivated; reinf ne-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature -	iorced iorced oforced QTY per se 1 1 1 1 1 1 1
For glider mechanism it is recommended to reinforced pedestal of Reinforced swivels options for glider mechanisms Glider Lock BOM Part	is durability, use Aluminium columns only. Aluminium columns 0 027 02 20112 65 Sv 027 02 20132 65 0 027 02 20142 01 Sv 027 02 20142 65 0 027 02 20142 65 Sv 027 02 20172 65 0 027 02 20172 65 Sv 027 02 20172 65 0 007 03 00011 00 Re 418 03 00002 10 418 03 00003 10 Mi 418 03 00005 09 418 03 00006 10 Br 990 15 00141 10 991 15 00095 10 Nu	vivel-column f. con vivel-column f. con vivel-	Lentil base 5 sta e-base 112,5/ 66lg x Ø50 tapered; alu nature - passivated; reinf e-base 132,5/ 86lg x Ø50 tapered; alu nature - passivated; reinf ne-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature -	iorced iorced ng nforced 0TY per se 1 1 1 1 1 1 5
For glider mechanism it is recommended to reinforced pedestal or Reinforced swivels options for glider mechanisms Glider Lock BOM Part Lock accessories	is durability, use Aluminium columns only. Aluminium column 027 02 20112 65 Sv 027 02 20132 65 Sv 027 02 20142 01 Sv 027 02 20142 65 Sv 027 02 20142 65 Sv 027 02 20172 01 Sv 027 02 20172 65 Sv 027 02 20172 65 Sv 027 03 00011 00 Re 418 03 00002 10 Mi 418 03 00005 09 Lo 418 03 00005 09 Lo 418 03 00005 10 Br 990 15 00141 10 Cr 007 03 00600 00 Br	vivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con escription elease adapter for etal plate small, 1 etal plate small	Lentil base 5 sta e-base 112,5/ 66lg x Ø50 tapered; alu nature - passivated; reinf e-base 132,5/ 86lg x Ø50 tapered; alu nature - passivated; reinf ne-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf ne-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126l	iorced iorced Ing GTY per se 1 1 1 1 1 2
For glider mechanism it is recommended to reinforced pedestal co Reinforced swivels options for glider mechanisms Glider Lock BOM Part Lock accessories Bowden cables	is durability, use Aluminium columns only. Aluminium column 0 027 02 20112 65 Sv 0 027 02 20132 65 Sv 0 027 02 20142 01 Sv 0 027 02 20142 01 Sv 0 027 02 20142 65 Sv 0 027 02 20172 01 Sv 0 027 02 20172 65 Sv 0 027 02 20172 65 Sv 0 027 03 00011 00 Re 418 03 00002 10 Mi 418 03 00003 10 Mi 418 03 00005 09 Lo 418 03 00006 10 Br 990 15 00141 10 Cc 991 15 00095 10 Nu 007 03 00800 00 or	coated column wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con escription elease adapter for letal plate small, 1 etal plate large, 1 jocking pin 1010 g racket Bowden ca ountersunk head s ut D439-B M16 powden Extract - 60 powden Extract - 60	Lentil base 5 sta e-base 112,5/ 66ig x Ø50 tapered; alu nature - passivated; reinf e-base 132,5/ 86ig x Ø50 tapered; alu nature - passivated; reinf he-base 142,5/ 96ig x Ø50 tapered; alu nature - passivated; stror e-base 142,5/ 126ig x Ø50 tapered; alu nature - passivated; stror e-base 172,5/126ig x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126ig x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126ig x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126ig x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126ig x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126ig x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126ig x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126ig x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126ig x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126ig x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126ig x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126ig x Ø50 tapered; alu nature - passivated; reinf 010 glider lock 010 glider lock 010 glider lock 020 mm length for all blockable gas springs 00 mm length for all blockable gas springs	iorced iorced ng iforced 1 1 1 1 1 6 2 1 1 1
For glider mechanism it is recommended to reinforced pedestal or Reinforced swivels options for glider mechanisms Glider Lock BOM Part Lock accessories	is durability, use Aluminium columns only. Aluminium column 0 027 02 20112 65 Sv 027 02 20132 65 0 027 02 20142 01 Sv 027 02 20142 65 0 027 02 20142 65 Sv 027 02 20172 65 0 027 02 20172 65 Sv 0 027 03 00011 00 Re 418 03 00002 10 Mi 418 03 00005 09 Lo 418 03 00005 10 Br 990 15 00141 10 Cc 991 15 00095 10 Nu 007 03 00600 00 Br 007 03 00800 00 or 007 03 00014 17 Le	coated column wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con etal plate small, 1 etal plate small, 1 etal plate small, 1 etal plate large, 1 boking pin 1010 gl acket Bowden ca buntersunk head s buntersunk head s buntersunk head s bunterstract - 60 bowden Extract - 80 ever with round he	Lentil base 5 sta e-base 112,5/ 66lg x Ø50 tapered; alu nature - passivated; reinf e-base 132,5/ 86lg x Ø50 tapered; alu nature - passivated; reinf ne-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf ne-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/126lg x Ø50 tapered; alu nature	iorced iorced inforced GTY per se 1 1 1 1 1 2 2 1
For glider mechanism t is recommended to reinforced pedestal co options for glider mechanisms Glider Lock BOM Part Lock accessories Bowden cables	is durability, use Aluminium columns only. Aluminium column 0 027 02 20112 65 Sv 0 027 02 20132 65 Sv 0 027 02 20142 01 Sv 0 027 02 20142 65 Sv 0 027 02 20142 65 Sv 0 027 02 20172 01 Sv 0 027 02 20172 65 Sv 0 027 03 00011 00 Re 418 03 00002 10 Mi 418 03 00005 09 Lo 418 03 00005 09 Lo 418 03 00005 10 Br 990 15 00141 10 Cc 991 15 00095 10 Nu 007 03 00014 17 Le 007 03 00015 17 or	coated column wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con vivel-column f.	Lentil base 5 sta e-base 112,5/ 66lg x Ø50 tapered; alu nature - passivated; reinf e-base 132,5/ 86lg x Ø50 tapered; alu nature - passivated; reinf he-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf 010 glider lock ider ble-1010 glider screw 8.8 ISO M6x10; DIN 7500 00 mm length for all blockable gas springs ad f. release adapter, 150 mm surface: powder coated black ad f. release adapter, 150 mm surface: stainless steel polished ad f. release adapter, 180 mm surface: powder coated black	iorced iorced iforced iforced 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
For glider mechanism t is recommended to reinforced pedestal co options for glider mechanisms Glider Lock BOM Part Lock accessories Bowden cables	is durability, use Aluminium columns only. Aluminium column 027 02 20112 65 Sv 027 02 20132 65 Sv 027 02 20142 01 Sv 027 02 20142 05 Sv 027 02 20142 65 Sv 027 02 20172 01 Sv 027 02 20172 65 Sv 027 02 20172 65 Sv 027 03 00011 00 Re 418 03 00002 10 Mi 418 03 00005 09 Lo 418 03 00005 09 Lo 418 03 00005 10 Br 990 15 00141 10 Cc 991 15 00095 10 Nt 007 03 00014 17 Le 007 03 00014 17 Le 007 03 00014 17 Le 007 03 00015 17 or 007 03 00015 30 or	coated column wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con wivel-column f. con escription elease adapter for letal plate small, 1 letal plate small, 1 letal plate small, 1 letal plate small, 1 easket Bowden ca but D439-B M16 bwden Extract - 66 bwden Extract - 66 bwden Extract - 80 wer with round he ever with round he ever with round he	Lentil base 5 sta e-base 112,5/ 66lg x Ø50 tapered; alu nature - passivated; reinf e-base 132,5/ 86lg x Ø50 tapered; alu nature - passivated; reinf e-base 142,5/ 96lg x Ø50 tapered; alu nature - passivated; stror e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; stror e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf e-base 172,5/ 126lg x Ø50 tapered; alu nature - passivated; reinf 010 glider lock 010 glider lock 010 glider lock 02 mm length for all blockable gas springs 03 mm length for all blockable gas springs 04 f. release adapter, 150 mm surface: powder coated black ad f. release adapter, 150 mm surface: stainless steel polished	iorced iorced aforced 1 1 1 1 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1